

LIMITI D'IMPIEGO

- Temperatura liquido fino a 35°C
(per un uso domestico secondo EN 60335-2-41)
Temperatura max. liquido: 35°C (per altri impieghi)
- Profondità d'immersione 8 mt.
- Livello min. d'aspirazione 80 mm

MOTORE

- Isolamento Classe F
- Protezione IP 68
- Protettore termico
- Cavo alimentazione 10 mt.

MATERIALI

- | | |
|---------------------------|---|
| - Corpo motore | Acciaio Inox |
| - Corpo pompa | Ghisa |
| - Girante alta | Acciaio Inox |
| - Albero motore | Acciaio Inox |
| - Trituratore | Acciaio Inox |
| - Doppia tenuta meccanica | Ceramica/Grafite/NBR
Silicio/Silicio/NBR |

OPERATING CONDITIONS

- Liquid temperature up to 35°C
(for home use according to EN 60335-2-41)
Temperature max. liquid: 35°C (for other uses)
- Submersion depth 8 mt.
- Min. suction level 80 mm

MOTOR

- Insulation Class F
- Protection IP 68
- Thermal protector
- Power cable 10 mt.

MATERIALS

- | | |
|--------------------------|---|
| - Motor body | Stainless Steel |
| - Pump body | Cast Iron |
| - High impeller | Stainless Steel |
| - Shaft with rotor | Stainless Steel |
| - Shredder | Stainless Steel |
| - Double mechanical seal | Ceramic/Graphite/NBR
Silicon/Silicon/NBR |

TIPO - TYPE**TRIT 1500**

P1	1100 W
Voltage	230 V
Frequency	50 Hz
Ampere	6 A
Q max.	280 l/1'
H max.	14 m
DNM - DNA	2"
Dimensions (P x L x H)	240 x 290 x 490 mm
Weight	21,1 kg

